

Stony Point® NATURAL LEDGE

Uses

Interior and exterior adhered veneer, including house fronts, commercial facades, foundations, columns, chimneys, fireplaces and surrounds, hearths, exterior and interior walls, outdoor kitchens and fireplaces.

Geology

Sandstone

Color Range

Buff, chocolate brown, tan, burgundy, and gray

Finish

Natural weathered face;
Sawn back

Dimensions (Average)

Piece size varies:
Length: 3"-16"
Height: 1½"-5"
Thickness: ¾"-1½"

Weight

Approx. 14 lbs/SF,
based on 1½" thick piece

Coverage

Corners available in 20 LF and 100 LF. Cover based on 1/2" mortar joint. Allow for 20% waste, when using a dry-stack application.



ASTM Data

Water Absorption: 1.71%
Density: 154.2 lbs/CF
Modulus
of Rupture: 1,040 psi
Compressive
Strength: 15,860 psi

DRystack



MORTARED



MasterCutNaturalStone.com

MCT2018.SP.NL.1

This document serves as a general guideline and the information provided within is not meant for exact structural specifications. MasterCut Natural Stone has neither liability, nor can be held responsible, to any person or entity for any misunderstanding, misuse, or misapplication that would cause loss or damage of any kind, including loss of rights, materials, personal injury, or alleged injury to be caused directly or indirectly by the information contained in this document. Images serve only as a general representation of the material and approval of the product should be based on the awareness of potential range of color and other characteristics.

Copyright © 2018, MasterCut Natural Stone. ASTM and the ASTM logo are registered trademarks of ASTM International. All rights reserved.

